

Befestigungsschrauben / Anziehdrehmomente

Fixing screws / Tightening torque

Vis pour fixation / Couple de serrage

Senkschrauben / Countersunk screws / Vis à tête conique				Techn. Daten / Technical data / Données techniques		
Wendeschneid- platten-Form Insert form Forme de plaquette	Senkschraube Countersunk screw Vis à tête conique Best.-Nr. Order No. No de cde.	Drehmomentschl. Torque screwdriver Clé dynamométrique Best.-Nr. Order No. No de cde.	Bedienschlüssel Service key Clé de service Best.-Nr. Order No. No de cde.	Anziehdrehmoment Torque Couple de serrage	Torx-Größe Torx-size Dimension Torx	
	20	115 535	415 508	115 591	0,9 Nm	T 7
	21	115 676	415 514	115 590	1,2 Nm	T 8
	37	115 676	415 514	115 590	1,2 Nm	T 8
	38	215 149	415 543	215 150	5,0 Nm	T 20
	39	115 673	415 510	115 664	3,0 Nm	T 15
	47	315 324	–	115 537	0,5 Nm	T 6
	64	115 673	415 510	115 664	3,0 Nm	T 15
	89	115 676	415 514	115 590	1,2 Nm	T 8
	90	115 531	415 514	115 590	1,2 Nm	T 8
	91	115 802	415 514	115 590	1,2 Nm	T 8
	101	115 676	415 514	115 590	1,2 Nm	T 8
	103	115 673	415 510	115 664	3,0 Nm	T 15
	104	215 149	415 543	215 150	5,0 Nm	T 20
	105	215 149	415 543	215 150	5,0 Nm	T 20
	111	115 531	415 514	115 590	1,2 Nm	T 8
	112	115 672*	415 510	115 664	3,0 Nm	T 15
	112	115 673	415 510	115 664	3,0 Nm	T 15
	113	215 149	415 543	215 150	5,0 Nm	T 20
	114	215 149	415 543	215 150	5,0 Nm	T 20
	145	415 277	415 508	115 591	0,9 Nm	T 7
	161	115 676	415 514	115 590	1,2 Nm	T 8
	163	115 673	415 510	115 664	3,0 Nm	T 15
	210	215 387	415 507	115 537	0,6 Nm	T 6
	211	215 377	415 507	115 537	0,6 Nm	T 6
	262	215 987	415 514	115 590	1,2 Nm	T 8
	264	115 673	415 510	115 664	3,0 Nm	T 15
	267	115 673	415 510	115 664	3,0 Nm	T 15
	278	215 393	415 510	115 664	3,0 Nm	T 15
	282	115 673	415 510	115 664	3,0 Nm	T 15
	283	215 911	415 510	115 664	3,0 Nm	T 15
	284	415 686	415 543	215 150	5,0 Nm	T 20
	286	415 130		415 121		T 25
	304	215 392	415 543	215 150	5,0 Nm	T 20
	394	215 915	415 514	115 590	1,2 Nm	T 8
	395	215 985	415 514	115 590	1,2 Nm	T 8
	396	415 320	415 510	115 664	3,0 Nm	T 15
	397	215 149	415 543	215 150	5,0 Nm	T 20
	411	415 420		115 591		T 7

* kurze Ausführung / short version / version courte



Z


Befestigungsschrauben / Anziehdrehmomente

Fixing screws / Tightening torque

Vis pour fixation / Couple de serrage

Spannbolzen / Clamping bolt / Boulon de serrage			Techn. Daten / Technical data / Données techniques	
Wendeschneid- platten-Form Insert form Forme de plaquette	Spannschraube / Spannbolzen Clamping screw / Clamping bolt Vis de serrage / Boulon de serrage Best.-Nr. Order No. No de cde.	Bedien Schlüssel Service key Clé de service Best.-Nr. Order No. No de cde.	Anziehdrehmoment Torque Couple de serrage	SW Type A
75	315 860	415 578		s3
123	315 463	415 578		s3
124, 134	215 566	415 578	ca./aprox./approx. 0,6 Nm	s3
125, 136	215 581	415 164		s4
133	115 775	115 575		s2,5
134	115 776	115 630	0,6 Nm	s3
137	315 805	415 165		s5
171	315 437	415 577		s2,5
287	315 977	415 164		s4
340	315 463	415 578		s3
368	415 205**	415 540		T 9

Wendeschneid- platten-Form Insert form Forme de plaquette	Senkschraube ① Countersunk screw Vis à tête conique Best.-Nr. Order No. No de cde.	Torx-Größe / Schlüsselweite Torx size / Key size Dimension Torx / Dim. de la clé	Spannbacken ② Clamping jaws Mors de serrage Best.-Nr. Order No. No de cde.
47	315 324	T 6	315 323
325	315 321	0,5 x 3	315 320



Z